



Box types	800	1100	1450
<p>Straight-line box</p>	A : 160 - 800 mm B : 100 - 800 mm E : 70 - 390 mm	A: 340/160 - 1100 mm B: 100 - 900 mm E: 170/70 - 540 mm	A: 420/220 - 1450 mm B: 170 - 900 mm E: 200/100 - 710 mm
<p>Crash-lock bottom box</p>	A: 170 - 800 mm B: 170 - 800 mm E: 80 - 390 mm	A: 340/170 - 1100 mm B: 170 - 900 mm E: 80 - 540 mm	A: 420/220 - 1450 mm B: 170 - 900 mm E: 200/100 - 710 mm
<p>Double-wall box</p>	A: 200 - 800 mm B: 100 - 800 mm D: 30 - 150 mm E: 80 - 620 mm	A: 200 - 1100 mm B: 100 - 800 mm D: 30 - 150 mm E: 80 - 950 mm	A: 320 - 1450 mm B: 100 - 800 mm D: 30 - 150 mm E: 200 - 1300 mm
<p>4-corner box</p>	A: 150 - 800 mm B: 160 - 800 mm H: 25 - 120 mm	A: 340/160 - 1100 mm B: 160 - 800 mm H: 25 - 150 mm	A: 280 - 1450 mm B: 180 - 800 mm H: 25 - 150 mm
<p>4-corner box with lid</p>	A: 250 - 750 mm B: 160 - 450 mm H: 25 - 120 mm	A: 330 - 1100 mm B: 160 - 450 mm H: 25 - 150 mm	A: 430 - 1450 mm B: 180 - 800 mm H: 25 - 150 mm
<p>6-corner box</p>	A: 270 - 700 mm B: 160 - 450 mm H: 25 - 120 mm	A: 370 - 1100 mm B: 160 - 450 mm H: 25 - 150 mm	A: 430 - 1450 mm B: 180 - 800 mm H: 25 - 150 mm

Thinking of solid board and corrugated flute packaging in mind, with special design of upper driven carriers, it allows to run both materials with competitive productivity and utmost finishing quality.

- C:** Without pre-folding section suitable for straight-line boxes.
- AC:** Without pre-folding section suitable for straight-line, crash-lock bottom & double wall boxes.
- PC:** Suitable for straight-line, crash-lock bottom & double wall boxes.
- SL:** Suitable for straight-line, crash-lock bottom, double wall, 4 & 6-corner boxes.

Specification	800			1100			1450		
TECHNOFOLD	AC	PC	SL	AC	PC	SL	AC	PC	SL
Material	200-800 g/m ²			200-1200 g/m ²			200-1200 g/m ²		
Corrugated type	N, E, F & B			N, E, F & B C			N, E, F & B C		
Speed	300 m/min			300 m/min			300 m/min		
Glue type	Water-based			Water-based			Water-based		
Blank width	160-800 mm			340-1100 mm			340-1450 mm		
Installation	AC	PC	SL	AC	PC	SL	AC	PC	SL
Length	14.3 m	16.6 m	16.6 m	15.1 m	17.4 m	17.4 m	16.6 m	18.9 m	18.9 m
Width	1.45 m	1.45 m	1.56 m	1.75 m	1.75 m	1.85 m	2.1 m	2.1 m	2.25 m
Height	1.4 m	1.4 m	1.4 m	1.5 m	1.5 m	1.5 m	1.5 m	1.5 m	1.5 m
Weight	7 Ton	7.5 Ton	8.1 Ton	8 Ton	9 Ton	9.6 Ton	10 Ton	10.8 Ton	11.4 Ton
Power supply	18 kW	18 kW	18 kW	18 kW	26 kW	26 kW	26 kW	26 kW	26 kW
Air compressor capacity	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h	10 m ³ /h